

# 010-1000 Rotating Lever Handle



These robust exterior and interior door handles are fabricated from high strength plate steel and feature modular attach/quick detach drive details and offer 1000 hour Cass protection with a soft touch coating.

**DESIGNED FOR:**

- Entrance and rear door applications for heavy-duty vehicles
- Interior and exterior applications
- Medium to heavy duty doors of 23-455 kg (50-1000 lbs.)

**Global Locations:**

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
www.trimarkcorp.com

**TriMark Europe**  
Unit 3  
Sence Court  
Bardon Hill  
Coalville LE67 1GZ  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
www.trimarkeu.com

**TriMark (Xuzhou)**  
Building A5 Jingwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation



TriMark Corporation

### FEATURES/BENEFITS:

- Heavy duty construction

### AVAILABLE:

- A variety of sizes and forms available
- Customization features available: Please inquire
  - ◆ Length and forming of handle
  - ◆ Handle materials

### MATERIAL:

- Standard — high strength steel construction
- Available with advanced lightweight aluminum alloy

### FINISH

- Standard low gloss black powder coated
- Mil-Spec soft grip nylon coated handle
- 1000 hour corrosion protection

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

**U.S. Design Patents: D596,917 / D615,383 / D615,841**



For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

