

Product Performance Summary

050-0600 Single Rotor Compartment Latch

Cycle Test:

The 050-0600 Single Rotor Latch meets cycle goal of 10,000 cycles, when cycled with a 50 lb (222N) simulated door seal load.

Release efforts at both inside and outside release locations were consistent throughout cycle life and remained < 40 lbf (177N)

(Striker bolt load may vary depending on application, which may vary life of latch)

Tensile Load Test:

Latch meets transverse loads in primary position of 750 lbf.

(Latch must be used with a TriMark approved striker bolt - reference 070-0400 12mm Diameter Striker Bolt)

NOTE:

The Product performance values shown are intended to be applied as a general guideline only, as specific applications and installation may affect the results. It is recommended that the Customer request a sample and conduct their own testing to determine the suitability of the Product for the intended purpose and specific application. Strength data is given as maximum loads at which the product is operable, however no safety factor has been applied.

Additional Testing information is available upon request.



500 Bailey Avenue
P.O. Box 350
New Hampton, IA 50659
United States
Tel: +1 641-394-3188
Fax: +1 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker Road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com