030-7150 Plastic Rectangular Paddle Handle





This 030-7150 Plastic Rectangular Paddle Handle is designed for use on personnel and compartment doors for light to medium duty, on or off-road applications. The paddle rotation drives a plunger output which allows for a direct latch release providing a compact and low-cost access solution.

DESIGNED FOR:

 Use in a direct latch release application or in conjunction with a bell crank or single point remote actuation



Global Locations:

TriMark Corporation 500 Bailey Avenue P.O. Box 350 New Hampton, Iowa 50659 United States Tel: 641-394-3188 Fax: 641-394-2392

Tel: 641-394-3188 Fax: 641-394-2392 1-800-447-0343 www.trimarkcorp.com Tri*Mark* Europe Cedar Court

Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

Tri*Mark* (Xuzhou)

www.trimarkcn.com

Building A5 Jingwu Road Xuzhou Economic Development Zone Xuzhou, Jiangsu 221004 PR China Tel: +86 516 8773 0018 Fax: +86 516 8773 0058







030-7150 Plastic Rectangular Paddle Handle

FEATURES/BENEFITS:

- Non-handed configuration allows for universal applications
- Interior or exterior applications
- The handle is rigid when locked
- Readily adaptable to a variety of doors with an adjustable bolt and nut

AVAILABLE:

- Lock can be keyed to match other TriMark door products with KeyOne Plus™ for a single-key system, keyed alike or provided non-locking
- With gasket for maximum water resistance



MATERIAL:

- Handle, paddle and actuator: Engineered plastic withstands corrosion and UV exposure
- Spring: Non-corrosive stainless steel
- Lock Cam Fastener, drive screw and nut: Steel

FINISH

- Standard black color
- Zinc plated clear chromate steel components

INSTALLATION:

- Easy installation with (3) #10-14 high performance thread forming fasteners (not included). Mounting torque not to exceed 40 in-lbs. (4.52 N-m)
- Mounting bracket (not included)

CAUTION: Product does not meet the locking requirements for FMVSS 206 (ECE R11).

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit www.trimarkcorp.com







