



The compact 050-7180 10mm Single Rotor Latch with Finger Release is designed for compartment door applications for offhighway vehicles that require a simple and compact rotary latch with a finger release.

DESIGNED FOR:

 Access panels and hoods for light duty doors up to 23Kg (50 lbs.) with door seal pressures no greater than 7 Kg (15 lbs.)

Global Locations:

TriMark Corporation 500 Bailey Avenue P.O. Box 350 New Hampton, Iowa 50659 **United States** Tel: 641-394-3188 Fax: 641-394-2392 1-800-447-0343

www.trimarkcorp.com

TriMark Europe Cedar Court Walker road Bardon Hill Coalville LE67 1TU United Kingdom Tel: +44(0)1530 512460 Fax: +44(0)1530 512461 www.trimarkeu.com

TriMark (Xuzhou) Building A5 Jingwu Road Xuzhou Economic Development Zone Xuzhou, Jiangsu 221004 PR China Tel: +86 516 8773 0018 Fax: +86 516 8773 0058

www.trimarkcn.com



TriMark. Interactive. Product. Selector



050-7180 10mm Single Rotor Latch With Finger Release

FEATURES/BENEFITS:

- Compact size and shape; allows maximum use of door space
- Two position rotary function
- Standard black finish reduces the need for secondary painting

AVAILABLE:

- Versions are available to allow application flexibility
- With and without direct release inside levers
- With left and right variants; provides application flexibility (right hand shown)

MATERIAL/FINISH:

- Black plated steel case halves
- Cam and finger release: Heat treated steel

For more information visit www.trimarkcorp.com

INSTALLATION:

 Easy to install -- recommended mounting fastener
(2) M5 x 1.0 flat or oval head fasteners are required (not included)

USE WITH:

• 070-7100 10 mm Striker Pin

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

Caution: Latch does not meet FMVSS 206 (ECE R11) load requirements.

