



The compact 050-7200 10mm Single Rotor Latch with Dual Trip Levers is designed for operator and compartment door applications for off-highway vehicles. Offering a direct push button handle release with remote cable or rod actuated inside release providing expanded application flexibility.

DESIGNED FOR:

 Light to medium duty doors up to 45Kg (100) lbs.) with door seal pressures no greater than 20 Kg (44 lbs.)



Global Locations:

TriMark Corporation

500 Bailey Avenue P.O. Box 350 New Hampton, Iowa 50659 United States Tel: 641-394-3188 Fax: 641-394-2392 1-800-447-0343 www.trimarkcorp.com

TriMark Europe

Cedar Court Walker road Bardon Hill Coalville LE67 1TU United Kingdom Tel: +44(0)1530 512460 Fax: +44(0)1530 512461 www.trimarkeu.com

TriMark (Xuzhou)

Building A5 Jingwu Road Xuzhou Economic **Development Zone** Xuzhou, Jiangsu 221004 PR China Tel: +86 516 8773 0018 Fax: +86 516 8773 0058 www.trimarkcn.com

TriMark **TriMark Corporation**

A TriMark.

FEATURES/BENEFITS:

- Compact size and shape; requires minimum use of door space
- Standard black finish reduces the need for secondary painting
- Two position rotary function

AVAILABLE:

- Versions are available to allow direct or remote actuation from exterior push button or paddle handles
- With left and right variants; provides application flexibility (right hand shown)

MATERIAL/FINISH:

- Black plated steel case halves
- Cam and catch: Heat treated steel

050-7200 10mm Single Rotor Latch With Dual Trip Levers

INSTALLATION:

• Easy to install -- recommended mounting fastener (2) M8 x 1.25 flat or oval head fasteners are required (not included)

USE WITH:

• 070-7100 10 mm Striker Pin

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

CAUTION: Latch does not meet FMVSS 206 (ECE R11) load requirements



