

200-7100 Hinge Assembly - Aluminum



This aluminum hinge is designed for light-duty off-highway vehicle applications on storage compartments or hinged windows.

Global Locations:

TriMark Corporation
500 Bailey Avenue
P.O. Box 350
New Hampton, Iowa 50659
United States
Tel: 641-394-3188
Fax: 641-394-2392
1-800-447-0343
www.trimarkcorp.com

TriMark Europe
Cedar Court
Walker road
Bardon Hill
Coalville LE67 1TU
United Kingdom
Tel: +44(0)1530 512460
Fax: +44(0)1530 512461
www.trimarkeu.com

TriMark (Xuzhou)
Building A5 Jingwu Road
Xuzhou Economic
Development Zone
Xuzhou, Jiangsu
221004 PR China
Tel: +86 516 8773 0018
Fax: +86 516 8773 0058
www.trimarkcn.com



TriMark. Interactive. Product. Selector



TriMark



TriMark Corporation

FEATURES/BENEFITS:

- Designed to be used vertically mounted with same type of fixing at both ends
- Mounting configurations (2) M8 bolt, 76mm (3.00") mounting pattern

MATERIAL/FINISH:

- Die cast aluminum material
- Black or grey powder coated

INSTALLATION:

- Installs with either suitable M8 fixing bolts or mushroom caps for glass mounting (not included)
- Recommended mounting fastener torque to be 6.7 - 7.9 N-m (59 to 70 in-lbs.)

Individual part dimensions are for reference only. Refer to individual part drawings for complete dimensions, specifications, and installation procedures. Engineering assistance and application drawings are available.

For more information visit
www.trimarkcorp.com

