

# 500-1350 PKE System (Passive Keyless Entry - Unsealed)



**TriMark's third generation of Systems** consists of a selection of compatible components that allow for complete keyless entry for on- or off-highway vehicle applications. It features Passive Keyless Entry (PKE) and offers optional vehicle mobilization/immobilization and keyless push button start.

## How does passive keyless entry/start work?

No FOB button presses are required, simply placing a hand into the door handle or within range (30 mm) of the external capacitive sensing puck will wake up the PKE controller. The controller sends out a low-frequency (LF) signal, all FOBs within range respond with their serial numbers using a radio frequency (RF) signal at 433 MHz. The controller compares the serial numbers against a stored list of authorized FOB's. The LF messaging also uses a random numbering scheme back and forth to prevent cyber attacks. If an authorized FOB is within range, the door automatically unlocks.

The FOB's also have typical lock/unlock buttons that can be used from up to 50 meters using RF signals. This messaging is encrypted - the FOB must decrypt the message and send back an appropriate response before the PKE controller will unlock the door.

The keyless start function is facilitated using LF/RF messaging a second time to ensure an authorized FOB is within range inside the vehicle using the same protocol. The controller then communicates to another SAE J1939 device that it's appropriate to mobilize the vehicle also using encrypted messages. The combination of LF challenge and RF response delivers low power consumption and long battery life.

This system allows for standardized hardware architecture and includes a common controller and other peripheral modules. This hardware is tested and validated and can be adapted to other applications with a high level of confidence.



## FEATURES/BENEFITS:

- Keyless-entry security and convenience for access door systems through a 'state of the art' electronic interface for the ultimate in end user convenience, functionality and security
- Passive Keyless Entry (PKE) provides for "hands free" unlocking
- Rugged and durable construction - compliant to on-road, off-road, and industrial environmental requirements
- Independent control of multiple door zones
- SAE J1939 at 250K/500K/1M or RVC to enable communications with other modules
- Locking/unlocking confirmation
- Lighting and auxiliary output control



TriMark. Interactive. Product. Selector

## Global Locations:

**TriMark Corporation**  
500 Bailey Avenue  
P.O. Box 350  
New Hampton, Iowa 50659  
United States  
Tel: 641-394-3188  
Fax: 641-394-2392  
1-800-447-0343  
www.trimarkcorp.com

**TriMark Europe**  
Unit 3  
Sence Court  
Bardon Hill  
Coalville LE67 1GZ  
United Kingdom  
Tel: +44(0)1530 512460  
Fax: +44(0)1530 512461  
www.trimarkeu.com

**TriMark (Xuzhou)**  
Building A5 Jingwu Road  
Xuzhou Economic  
Development Zone  
Xuzhou, Jiangsu  
221004 PR China  
Tel: +86 516 8773 0018  
Fax: +86 516 8773 0058  
www.trimarkcn.com



TriMark



TriMark Corporation



TriMark Corporation

### 530-0400 PKE e-FOB:

- Stylish 4-button PKE FOB - operates at 125 kHz (PKE) and 433 MHz (RF) transmission (Compliant to FCC-Part 15 and EU RF requirements)
  - 4 button FOB can be used for other functions such as illumination of work lights as you approach the machine for safe entry or service of the machine
  - The key FOB can also be used as a normal RF keyless entry so unlocking/locking via button presses is possible - range is approximately 50 meters
- High security with random numbering scheme back and forth between the FOB's and controller to prevent cyber attacks
- Customized graphics possible (buttons and logos)
- Can sync up to 50 FOB transmitters per vehicle
- Passive Start/Immobilization - authorized FOB needs to be located inside the vehicle to allow Passive Start. If the correct FOB is not within range of the internal antenna(s), the vehicle cannot be started.
- 2 FOB styles available: wire form key holder or high style chrome key holder

### 510-0350 PKE e-CONTROLLER (Unsealed):

- Unsealed enclosure with AMP/VAL-U-LOK connectors – 4, 6, 10, 12, 14 and 24 pin connectors
- Enables distributed functionality, such as multiple door control and ignition immobilization, via vehicle multiplex communication

### AVAILABLE:

- Standard kit make up includes: (2) pre-paired PKE remote FOB transmitters, I/O module, external antenna and manual
- Multiplex or discrete communications
- Can add TriMark's 540-0100, 540-0110, or 540-0200 Keypad for true keyless operation
- Optional kits can include: wiring harnesses for all connection points, extra relays, switches, door contacts, actuators, mounting hardware, mounting brackets, door latches, and exterior door handles

For more information visit  
[www.trimarkcorp.com](http://www.trimarkcorp.com)

### WARNING:

Immediately dispose of used batteries and keep away from children. Do NOT dispose of batteries in household trash.

Even used batteries may cause severe injury or death.

Call a local poison control center for treatment information.

### 590-1200 PKE ANTENNA:

- RFID Antenna (125 kHz) - 1 external for cab entry (PKE) and 1-2 for interior; immobilization and push to start
- Potted construction ensures environmental protection and durability performance – can be used in exterior or interior locations
- Custom mounting brackets available

### REMOTE START:

- Optional Remote Start available with select engines. (Custom software is required to communicate with Engine Control Unit (ECU))

### INSTALLATION:

- 12 VDC operation
- I/O module is easily installed with (3) M4 screws (not included) and can be mounted in a concealed location



510-0350 e-Controller  
(Unsealed)



590-1200 PKE Antenna



530-0400 PKE e-FOB

Please refer to individual product codes and part drawings for complete dimensions, specifications, installation procedures, and related items. Engineering assistance and application drawings are available.

**Open-Source Software:** This product may contain embedded software from open-source communities. The open-source software (OOS), copyright, licensing terms and conditions are located at the following [link](#).

**U.S. Patent No. 7,034,655 / 8,350,669 / 8,976,014 / 10,385,594 // 10,909,785**

### ⚠ WARNING

- **INGESTION HAZARD:** This product contains a button cell or coin battery.
- **DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **Internal Chemical Burns** in as little as **2 hours**.
- **KEEP** new and used batteries **OUT OF REACH OF CHILDREN**
- **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body.

